



PERROT-KARDANKUPPLUNG PERROT CARDAN COUPLING

KKV Edelstahl/Stainless steel

Kardan V-Teil, zum Auf- und Anschweissen, Edelstahl
Cardan male coupling, for welding, stainless steel

Typ OPTIMA

Betriebsdruck / Operating pressure: 10 bar



Artikel/Grösse Article/Size	Gewicht Weight	Art-Nummer Part-Number
KKV 50 / OPTIMA	0,14	KT60000
KKV 70 / OPTIMA	0,30	KT60100
KKV 89 / OPTIMA	0,49	KT60200
KKV 108 / OPTIMA	0,61	KT60300
KKV 133 / OPTIMA	0,70	KT60400
KKV 159 / OPTIMA	1,10	KT60500

KKM Edelstahl/Stainless steel

Kardan M-Teil Edelstahl zum Auf- und Anschweissen, Kardanring + Hebelwerk verzinkt,
unmontiert

Cardan female coupling, stain less steel, for welding, cardan ring + leverage galvanized,
unassembled

TYP SUPRA

Betriebsdruck / Operating pressure: 10 bar



Artikel/Grösse Article/Size	Gewicht Weight	Art-Nummer Part-Number
KKM 50 / SUPRA	0,70	KK60003
KKM 70 / SUPRA	1,13	KK60103
KKM 89 / SUPRA	2,00	KK60203
KKM 108 / SUPRA	3,00	KK60303
KKM 133 / SUPRA	4,84	KK60403
KKM 159 / SUPRA	6,19	KK60503

KKM Edelstahl/Stainless steel

Kardan M-Teil, Edelstahl, zum Auf- und Anschweissen, unmontiert
Cardan female coupling, stain less steel, for welding, unassembled
Typ OPTIMA

Betriebsdruck / Operating pressure: 10 bar



Artikel/Grösse Article/Size	Gewicht Weight	Art-Nummer Part-Number
KKM 50 / OPTIMA	0,69	KK60001
KKM 70 / OPTIMA	1,09	KK60104
KKM 89 / OPTIMA	2,18	KK60204
KKM 108 / OPTIMA	2,96	KK60304
KKM 133 / OPTIMA	5,23	KK60404
KKM 159 / OPTIMA	6,08	KK60504

KKMM Edelstahl/Stainless steel

Kardan M-Teil Edelstahl zum Auf- und Anschweissen, Kardanring + Hebelwerk verzinkt, montiert
Cardan female coupling, stain less steel, for welding, cardan ring + leverage galvanized,
assembled
TYP SUPRA

Betriebsdruck / Operating pressure: 10 bar



Artikel/Grösse Article/Size	Gewicht Weight	Art-Nummer Part-Number
KKMM 50 / SUPRA	0,62	KK60001
KKMM 70 / SUPRA	0,63	KK60103
KKMM 89 / SUPRA	1,96	KK60203
KKMM 108 / SUPRA	2,84	KK60303
KKMM 133 / SUPRA	3,74	KK60403
KKMM 159 / SUPRA	4,85	KK60504

KKMM OPTIMA Edelstahl/Stainless steel

Kardan M-Teil, Edelstahl, zum Auf- und Anschweissen, montiert
Cardan female coupling, stain less steel, for welding, assembled
Typ OPTIMA

Betriebsdruck / Operating pressure: 10 bar



Artikel/Grösse Article/Size	Gewicht Weight	Art-Nummer Part-Number
KKMM 50 / OPTIMA	0,66	KK60002
KKMM 70 / OPTIMA	0,99	KK60102
KKMM 89 / OPTIMA	1,84	KK60202
KKMM 108 / OPTIMA	2,91	KK60302
KKMM 133 / OPTIMA	3,55	KK60402
KKMM 159 / OPTIMA	4,90	KK60502