

REGULUS & REGULUS OUTDOOR



CONTROLLER

SPECIFICATIONS:

- Power supply 220 VAC (indoor) -230 VAC (outdoor) / 50 Hz
- Output voltage: 24 VAC (0.5 A)
- Max total (including MV control): 24 VAC, (1.0 A)
- Dimensions Controller: 140 x 186 x 97 mm
Outdoor Box: 320 x 245 x 142 mm
- Weight: 1,5kg (indoor) - 3kg (outdoor) incl. transformer

AREAS OF APPLICATION:

Soccer fields, sports fields, hockey pitches, tennis courts, parks, private gardens

FEATURES:

- From 4 to 16 stations
- 8 independent irrigation programs with 6 start times each
- IoT WiFi ready
- Complete programming and operation via mobile APP possible
- Permanent memory
- Seasonal adjustment from 0 – 200 % by water budget function
- Watering calendar: Day of the week selection per program
- Up to 2 stations can be controlled at the same time with 2 programs
- All programs can be started directly via key switch
- Automatic, semi-automatic and manual start
- User-selectable language (EN, DE, FR, IT, ES, PL)
- The “Super Cap” option provides back up power for maintaining the current time and date in the event of a power cut for more than 24 hours (no batteries needed)
- All sensors incl. rain sensor can be managed in 5 different modes incl. key switch
- Programmable rain delay between stations (from 1 sec to 2 min)
- Sector Scout function:
 - Incl. for Perrot VP3 SC sprinklers for all installed stations
 - Parallel operation of two VP3 SC possible
 - Automatic position calibration of one or all stations possible
- Regulus outdoor with UV-resistant and waterproof housing, lockable and with integrated transformer 230V / 24VAC.



PERROT
Regnerbau Calw GmbH

Industriestrasse 19-29
D-75382 Althengstett

Tel. +49(0)7051/162-0
Fax +49(0)7051/162-133

perrot@perrot.de
www.perrot.de